

The Switch Stretch Wrapper Makes Your Buying Decision Easy!



DATE: May 2013

SWITCH MODELS LP-SW & HP-SW STANDARD FEATURES	COUSINS SWITCH	LANTECH Q300	WULFTEC SML 150	ORION FLEX LPE	ARPAC Pro-Series	PHOENIX PLP-2100	FOX C3
The ability to be easily converted to a fully automatic on site at a later date	YES	NO	NO	NO	NO	NO	NO
65" diameter turntable with heavy duty surround deck on LP model	YES	NO	NO	NO	NO	NO	NO
4500# turntable capacity	YES	NO	NO	NO	NO	NO	YES
Available in a high profile model for easier fork lift loading (model HP-SW)	YES	NO	YES	YES	YES	YES	YES
All AC variable frequency drives and motors	YES	NO	YES	YES	NO	NO	NO
Standard 67" x 67" maximum load size (up to a 96" diagonal)	YES	NO	NO	NO	NO	NO	NO
A unique pre-stretch film carriage that provides maximum film-to-rubber roller contact. The threading method always places the sticky side of the film against <u>both</u> the rubber rollers and the load.	YES	Has less film-to-rubber roller contact	NO	NO	NO	NO	NO
Three (3) separate wrap programs	YES	NO	NO	NO	NO	NO	NO
HMI operator interface with diagnostic ability	YES	NO	NO	YES	NO	NO	NO
Anti-fall devices for both the film carriage and optional A-Arm	YES	NO	NO	NO	NO	NO	NO
Safety electrical interlock that shuts the power off when the access door is opened for film threading.	YES	NO	NO	NO	NO	YES	YES
Film carriage anti-descent plate - stops the carriage movement if obstacle is detected	YES	NO	NO	YES	NO	NO	NO
One machine can be demonstrated and sold as either a semi-auto or full automatic	YES	NO	NO	NO	NO	NO	NO

Note: This information is based on competitive information available to the public and may be incorrect because of recent changes to specifications. Please check with the manufacturer for any recent revisions to their specifications.