

EXCLUSIVELY FROM



# THE SWITCH A-ARM

Cousins smart engineering has developed an advanced cut and hold device, the A-Arm. It provides significant productivity gains and safety benefits. This technology is only available on a Cousins machine.

Less film slippage means more consistent stretch and the "sticky" side of the film will always be against both the rubber rollers and the load where it belongs

All AC motors

- ❖ 65" diameter turntable
- ❖ 64" L x 64" W x 75" H max load size (90" diagonal)
- ❖ 4500# capacity
- ❖ Heavy-duty surround deck

**NOTE:** Available in a high profile turntable model with a 48" x 48" deck



THE SWITCH A-ARM  
MODEL LP-SWA

The A-Arm technology is available in a fully automated conveyORIZED system that will reduce labor costs at a very affordable price.



MODEL 3300-A

# THE SWITCH A-ARM DESIGN FEATURES/SPECIFICATIONS

## CONTROLS:

- ❖ **3 machines in 1** easy selection for Automatic / semi-automatic / top banding modes
- ❖ LCD Operator Interface with Diagnostics
- ❖ Cycle Pause & Reinforce Wrap
- ❖ Separate UP/DOWN Spiral Speed Controls
- ❖ 3 Separate Wrap Programs
- ❖ Selectable Reduced Film Tension parameters for wrapping top and/or bottom of light loads
- ❖ Emergency Stop button
- ❖ Wireless Remote Cycle Start/Stop
- ❖ 115 Volts 1 Phase 60 Hz 15 Amps
- ❖ **3 Year Warranty on Components**



## FILM CARRIAGE:

- ❖ Super Rapid Thread II™ 20" capacity pre-stretch film carriage
- ❖ Safety Door with auto power cut-off switch
- ❖ Special Film Threading Device – Uniquely orientates the sticky side of the film against the pre-stretch rollers and the inside on the load.
- ❖ ½ HP AC variable speed motor
- ❖ 33% to 313% fixed stretch capability
- ❖ Carriage Descent Safety Shut-Off Device
- ❖ Superior film-to-roller contact area
- ❖ **Lifetime warranty on pre-stretch rollers**



## TOWER DESIGN:

- ❖ Fully Enclosed & Guarded Motors
- ❖ No Exposed Cables
- ❖ Heavy Duty Formed/Structural Steel
- ❖ Electro-static powder coated paint finish
- ❖ **5 Year Warranty on Steel Fabrications**



## LOW PROFILE TURNTABLE:

- ❖ 4500# Capacity
- ❖ 1 – 12 RPM with Soft Start Acceleration
- ❖ ½ HP AC Variable Speed Drive
- ❖ Heavy Duty Surround Deck
- ❖ Forklift Tubes – Front and Rear
- ❖ Maintenance Free 48 Support Wheels
- ❖ 65" diameter
- ❖ Optional loading ramp 60" long x 48" wide complete with 10" level porch area available

