

STAR Pro SERIES N-TOPCon 144-cell MODULE

EG-580NT72-HLV

560~580W

KEY FEATURES



SMBB cell design
Super multi Busbar cells brings lower resistance and increased Busbar reflectance ensures higher power output



Low degradation
Adopt N-Type TOPCon cell technology, lower degradation and better temperature co-efficiency, greatly increased on generation performance




High Reliability
Strict in-house testing in PV Lab which is CNAS approved & TUV /VDE certified



Excellent Low-light Performance
Advanced solar cell and glass surface texturing technology allows for excellent performance in low-light environments

LINEAR PERFORMANCE WARRANTY


15 15 Year Product Warranty **30** 30 Year Linear Power Warranty




As a BloombergNEF Tier 1 and global leading manufacturer since 1998, EGING PV is committed to supplying reliable and durable PV products to customers to create together a greener planet.

EG-580NT72-HLV

Engineering Drawings



I-V Curves



Packing Configuration

Pieces per pallet	36
Size of packing (mm)	2320*1135*1255
Weight of packing (kg)	1022
Pieces per container	720
Size of container	40'HC

Electrical Characteristics

Power level	560	565	570	575	580
Pmax (W)	560	565	570	575	580
Vmp (V)	41.80	41.98	42.17	42.35	42.53
Imp (A)	13.40	13.46	13.52	13.58	13.64
Voc (V)	50.70	50.85	51.00	51.15	51.30
Isc (A)	14.19	14.25	14.31	14.37	14.43
Module efficiency (%)	21.67	21.87	22.06	22.25	22.45
Maximum system voltage (V)	1500				
Fuse Rating (A)	25				
Temperature coefficient Pmax (%/°C)	-0.30				
Temperature coefficient Isc (%/°C)	0.046				
Temperature coefficient Voc (%/°C)	-0.25				

STC: Irradiance 1000W/m², module temperature 25°C, AM=1.5

Working Characteristics

Power level	560	565	570	575	580
Pmax (W)	421	425	429	432	436
Vmp (V)	39.17	39.32	39.47	39.49	39.61
Imp (A)	10.75	10.81	10.87	10.94	11.01
Voc (V)	47.87	48.01	48.15	48.28	48.41
Isc (A)	11.40	11.46	11.52	11.59	11.65
Tolerance (%)	Pmax: ±3% Binning: ±5W Voc: ±5% Isc: ±5%				
NOCT (°C)	44 ±2				

NOCT: Conditions: Irradiance 800W/m², ambient temperature 20°C, wind speed 1m/s

Mechanical Characteristics

Number of cells	144pcs
Size of cell (mm)	182*91
Type of cell	N-type Mono
Thickness of glass (mm)	3.2
Type of frame	Anodized aluminum alloy
Junction box	IP68
Size of module (mm)	2278*1134*30
Weight (kg)	27
Cables/connectors	62930 IEC 131, 1*4mm²/EGing: E1-X, QC Solar: QC4.10-cd, Zerrun: Z4S, Renhe: RHC2xyzu
Length of Cable	Portrait: +300mm/-300mm
Fire class	Class C

Maximum Ratings

Operating Temperature(°C)	-40~85
Operating humidity(°C)	5~85
Allowable Hail Load	25mm ice-ball with velocity of 23m/s

Revised in March 2023 1st Edition

CAUTION: All rights and explain reserved by EGING PV.

Specifications included in this datasheet are subject to change without notice.

Made in China

Changzhou EGING Photovoltaic Technology Co., Ltd



Tel: 86-519-82585880

Zip: 213213

Add: No.18, Jinwu Road, Jintan Dist,
Changzhou City, Jiangsu Province.

Email: marketing@egingpv.com

Web: www.egingpv.com