

**A unique design to help you express your own individual style**

The unique design of this cooker hood introduces an individual look to your kitchen. Its bold lines will help you to express your own style.

Product Benefits & Features**Hood settings, made simple**

Your cooker hood functions can be easily reached with our mechanical controls. Adjust the light settings or the fan speed for fast, flexible cooking.

- Installation type: Chimney, width 60 cm
- Number of speeds: 3
- Maximum noise level (high/low): 68/49 dB(A)
- Push button controls with 3 speeds
- Air extraction or recirculation possible, charcoal filter included.
- Cooker hood lamps type and number: LED bulb, 2
- Grease filter type and number: Aluminium Cassette, 2

Better cleaning with less energy

Now you can enjoy enhanced cooking performance while using even less energy. Our cooker hood offers all the benefits you come to expect, including halogen light and effective fan. But now its Class B energy consumption rating means saving money on your electricity, too.

Cleaner air all round

This advanced cooker hood features a powerful motor that whisks away cooking fumes quickly. So you can enjoy a cleaner atmosphere for cooking, eating and relaxing.

**More visibility, less energy**

Energy-efficient LEDs are ideal for sociable areas like the kitchen, where lighting is used frequently and for long periods of time. Bright, long-lasting and incredibly energy-efficient, they're an essential feature in modern homes.

Product Specification

Product Installation	Built_In	Speeds	3
Product Typology	Cooker_Hood	Size	60
Product Class	Cooker_Hood	Motors n° of	1
Frequency	50/60	Minimum distance from cooking top ELECTRIC	50
Voltage	220-240	Minimum distance from cooking top GAS	65
Main colour	Stainless Steel	Lamp n° of	2
Required fuse (A)	10	Lamp type	LED bulb
Chimney colour	Stainless Steel	Type of filter	Aluminium Cassette
Height total	766		
Height max. external	1213		
Width mm	598		
Depth mm	500		
Weight net cleaner and accessories no packaging	13.85		
Cord length external	1.5		
Air outlet	150		
Capacity High	600		
Capacity Low	256		
Motor absorption	243		
Noise power High in dB(A)	68		
Noise power Low in dB(A)	49		
Noise power Recirculation High in dB (A)	70		
Noise power Recirculation Low in dB (A)	63		