

File name:

OBSOLETE_1995_MSI_MISC_SCREEN_LOCATOR_SECURITY_CODES.pdf

This product was distributed by the DME Company in the early 1990's.

DME does not offer any support or repairs for this product. The following pages contains the documentation which was provided when the DME Company distributed this product.

Contact American MSI Corporation directly for assistance with this product.

MTC System Screen Locator

Security

- Enter Password

Set Points

- Set Points
- Actual Temp
- Power Output
- Set Alarm
- Regulation
- Slave
- On / Off
- Error Display

Zone Setup Page 1 (LIMITS)

- Set Alarm
- Regulation
- Slave
- AMC
- PMC
- T/C
- PID Selection
- Zone On / Off
- Error Display

Zone Setup Page 2

- Set Boost Temps
- Set Auto Boost Temps*
- Set Stand By Temps
- Set Auto Stand By Temps*

Setup PID

- Adjust PID Loop
- Select PID Loop

Key Identification

- | | |
|-------------------------------------|--|
| <input type="checkbox"/> S Stand By | <input type="checkbox"/> C Clear Alarm |
| <input type="checkbox"/> B Boost | <input type="checkbox"/> + Increase |
| <input type="checkbox"/> I Start | <input type="checkbox"/> - Decrease |
| <input type="checkbox"/> O Stop | <input type="checkbox"/> ▲ Cursor |
| <input type="checkbox"/> E Exit | <input type="checkbox"/> ▼ Movement |

Temperature Graph

- Set Point
- Actual Temperature
- Temperature Graph

Power Graph

- Set Point
- Actual Temperature
- Power Percent Graph

System Setup

- Units (F/C)
- Softstart
- Bakeout
- Boost Times
- Stand By Times
- Print Out

Current Test*

- Current Test
- Save Test

* - Optional Features

Security Codes

Security codes are listed below for the operators' use:

LEVEL ONE: 6556

LEVEL TWO: 4711

LEVEL Three: 0322