

GATING STYLE	PAGE	GATE Ø	GATE SEAL OPTIONS	GATE SEAL PACKAGE
EXT. F-TYPE TORPEDO	07.01.020	Ø1.50	TS010001F + TP010001	TS010001FP
		Ø2.00	TS010002F + TP010001	TS010002FP
		Ø2.50	TS010003F + TP010001	TS010003FP
HOT SPRUE	07.01.030	Ø2.00	TS010004F	N/A
		Ø2.50	TS010004F1	N/A
		Ø3.00	TS010004F2	N/A
		Ø3.50	TS010004F3	N/A
		Ø4.00	TS010004F4	N/A
EXT. HOT SPRUE	07.01.040	Ø2.00	TS010005F	N/A
		Ø3.00	TS010005F1	N/A
		Ø4.00	TS010005F2	N/A
BI-MET. C-VALVE	07.01.050	Ø1.50 ~ Ø2.50	TS010006 + TSL010015 (Ø4 PIN)	TS010006P2
			* TS010006 + TSL010015-1 (Ø4 PIN)	* TS010006P6
		Ø1.90 ~ Ø3.40	TS010006 + TSL010001 (Ø5 PIN)	TS010006P
			* TS010006 + TSL010001-1 (Ø5 PIN)	* TS010006P4
EXT. BI-MET. C-VALVE	07.01.060	Ø1.50 ~ Ø2.50	TS010006 + TSL010016 (Ø4 PIN)	TS010006P3
			* TS010006 + TSL010016-1 (Ø4 PIN)	* TS010006P7
		Ø1.90 ~ Ø3.40	TS010006 + TSL010002 (Ø5 PIN)	TS010006P1
			* TS010006 + TSL010002-1 (Ø5 PIN)	* TS010006P5
BI-MET. BALLNOSE C-VALVE	07.01.070	Ø1.50 ~ Ø2.50	TS010033 + TSL010017 (Ø4 PIN)	TS010033P1
			* TS010033 + TSL010017-1 (Ø4 PIN)	* TS010033P4
		Ø1.90 ~ Ø3.60	TS010033 + TSL010003 (Ø5 PIN)	TS010033P
			* TS010033 + TSL010003-1 (Ø5 PIN)	* TS010033P3
HOT VALVE	07.01.080	Ø2.50	TS010007F	N/A
		Ø3.00	TS010008F	N/A
		Ø4.00	TS010009F	N/A
EXT. HOT VALVE	07.01.090	Ø2.50	TS010010F	N/A
		Ø3.00	TS010011F	N/A
		Ø4.00	TS010012F	N/A

\* FOR TRANSPARENT LENS APPLICATIONS (PC/PMMA)  
INJECTION PRESSURE NOT TO EXCEED 1600 BAR