

GATING STYLE	PAGE (NOZZLE STYLE)		GATE Ø	GATE SEAL OPTIONS	GATE SEAL PACKAGE
EXT. F-TYPE TORPEDO	08.01.020 (REGULAR)	08.01.025 (HEATER SLEEVE)	Ø2.00	TS010013F + TP010002	TS010013FP
			Ø2.50	TS010014F + TP010002	TS010014FP
			Ø3.00	TS010015F + TP010002	TS010015FP
HOT SPRUE	08.01.030 (REGULAR)	08.01.035 (HEATER SLEEVE)	Ø2.50	TS010016F	N/A
			Ø3.00	TS010016F1	N/A
			Ø3.50	TS010016F2	N/A
			Ø4.00	TS010016F3	N/A
			Ø5.00	TS010016F4	N/A
EXT. HOT SPRUE	08.01.040 (REGULAR)	08.01.045 (HEATER SLEEVE)	Ø3.00	TS010017F1	N/A
			Ø4.00	TS010017F3	N/A
			Ø5.00	TS010017F4	N/A
BI-MET. C-VALVE	08.01.050 (REGULAR)	08.01.055 (HEATER SLEEVE)	Ø1.50 ~ Ø3.10	TS010018 + TSL010004 (Ø5 PIN)	TS010018P2
				* TS010018 + TSL010004-1 (Ø5 PIN)	* TS010018P8
			Ø2.00 ~ Ø5.10	TS010018 + TSL010005 (Ø8 PIN)	TS010018P
				* TS010018 + TSL010005-1 (Ø8 PIN)	* TS010018P6
EXT. BI-MET. C-VALVE	08.01.060 (REGULAR)	08.01.065 (HEATER SLEEVE)	Ø1.50 ~ Ø3.10	TS010018 + TSL010006 (Ø5 PIN)	TS010018P3
				* TS010018 + TSL010006-1 (Ø5 PIN)	* TS010018P9
			Ø2.00 ~ Ø5.10	TS010018 + TSL010007 (Ø8 PIN)	TS010018P1
				* TS010018 + TSL010007-1 (Ø8 PIN)	* TS010018P7
BI-MET. BALLNOSE C-VALVE	08.01.070 (REGULAR)	08.01.075 (HEATER SLEEVE)	Ø1.50 ~ Ø3.10	TS010018 + TSL010018 (Ø5 PIN)	TS010018P5
				* TS010018 + TSL010018-1 (Ø5 PIN)	* TS010018P11
			Ø2.00 ~ Ø4.60	TS010018 + TSL010008 (Ø8 PIN)	TS010018P4
				* TS010018 + TSL010008-1 (Ø8 PIN)	* TS010018P10
HOT VALVE	08.01.080 (REGULAR)	08.01.085 (HEATER SLEEVE)	Ø4.00	TS010019F	N/A
			Ø5.00	TS010020F	N/A
EXT. HOT VALVE	08.01.090 (REGULAR)	08.01.095 (HEATER SLEEVE)	Ø4.00	TS010021F	N/A
			Ø5.00	TS010022F	N/A

\* FOR TRANSPARENT LENS APPLICATIONS (PC/PMMA)  
INJECTION PRESSURE NOT TO EXCEED 1600 BAR