

NOZZLE #	** POWER @ 220V
NZ01DB*A028	250W
NZ01DB*A048	300W
NZ01DB*A068	300W
NZ01DB*A088	350W
NZ01DB*A108	350W
NZ01DB*A128	350W
NZ01DB*A148	350W
NZ01DB*A168	400W
NZ01DB*A188	400W
NZ01DB*A208	450W

** REFER TO PAGE 13.08.010
FOR OTHER WATTAGE / VOLTAGE
EQUIVALENTS.

APPLICABLE GATING METHODS	NOZZLE #	NOZZLE EXPANSION ΔL			
		θ ΔT (PROCESS TEMP. - MOLD TEMP.)			
		150°C	200°C	250°C	300°C
EXT. F-TYPE TORPEDO HOT SPRUE EXT. HOT SPRUE HOT VALVE EXT. HOT VALVE	NZ01DB*A028	0.10	0.13	0.16	0.22
	NZ01DB*A048	0.13	0.18	0.22	0.29
	NZ01DB*A068	0.17	0.22	0.29	0.36
	NZ01DB*A088	0.20	0.27	0.35	0.43
	NZ01DB*A108	0.23	0.32	0.41	0.50
	NZ01DB*A128	0.27	0.37	0.47	0.57
	NZ01DB*A148	0.30	0.41	0.53	0.65
	NZ01DB*A168	0.34	0.46	0.59	0.72
	NZ01DB*A188	0.37	0.51	0.65	0.80
BI-MET. C-VALVE EXT. BI-MET. C-VALVE BI-MET. BALLNOSE C-VALVE	NZ01DB1A028	0.10	0.14	0.17	0.22
	NZ01DB1A048	0.14	0.18	0.23	0.29
	NZ01DB1A068	0.17	0.23	0.30	0.37
	NZ01DB1A088	0.21	0.28	0.36	0.44
	NZ01DB1A108	0.24	0.33	0.42	0.51
	NZ01DB1A128	0.28	0.38	0.48	0.59
	NZ01DB1A148	0.31	0.43	0.55	0.66
	NZ01DB1A168	0.35	0.47	0.61	0.74
	NZ01DB1A188	0.38	0.52	0.67	0.81
NZ01DB1A208	0.42	0.57	0.73	0.88	