



LP500M

LOW PRESSURE MULTI NOZZLE SERIES

Tonnage: 500

**Melt Unit:
423**

TECHNICAL SPECIFICATIONS

©2017 Milacron LLC. All Rights Reserved.
Pub Number: T4.1301.A.09.17

4165 Half Acre Rd.,
Batavia OH 45103
513.536.2000
info@milacron.com
www.milacron.com



LP500M-423		
	ENGLISH	METRIC
Clamp		
Clamp Tonnage	tons	500
	tonnes	454
Platen Size (H x V)	in	89 x 98
	mm	2,261 x 2,489
Distance Between Tie Bars	in	67.5 x 58.5
	mm	1,715 x 1,486
Tie Bar Diameter	in	7.5
	mm	191
Max. Clamp Opening (Daylight)	in	120
	mm	3,048
Clamp Stroke	in	108
	mm	2,743
Min. Mold Shut Height	in	12
	mm	305
Clamp Speed Max	in/sec	14
	mm/sec	356
Mold Carrying Capacity (Moving Platen)	lbs	35,000
	kg	15,876
Way Support System		Standard
Extruder		
Number of Extruders		1
Screw Diameter	in	4.5
	mm	114
L/D Ratio		30:1
Output HDPE or P.S. (total)	lbs/hr	900
	kg/hr	408
Drive Size	Hp	250
	kW	186.4
Barrel Heating\Cooling Zones		5
Barrel Cooling Type		Air Barrel Cooling

LP500M-423		
	ENGLISH	METRIC
Injection		
Number of Accumulators		1
Total Shot Weight (Shot Size) PS/HDPE	lbs	75/60
	kg	34/27
Accumulators Volume (Each)	in ³	2,300
	cm ³	37,690
Total Shot Volume	in ³	2,300
	cm ³	37,690
Pressure Maximum (Per Accum.)	psi	6,000
	bar	414
Total Number of Shot Sizes		16
Independent Nozzle Sequence		32
Nozzle		
Multiple Nozzles		As Required
Nozzle Spacing	in	6 x 6
	mm	152 x 152
Number of Nozzle Locations		180
Nozzle Heat Control Zones		32
Manifold Extension Heat Control Zones		20
Nozzle Hydraulic Controls		32

Notes

1) All machine dimensions and specifications are subject to change. Values are for reference only. All general assembly drawings or visuals included herein are for reference only. Please consult the general assembly drawing from a Milacron representative.


LP500M

LOW PRESSURE MULTI NOZZLE SERIES

Tonnage: 500

**Melt Unit:
423**

TECHNICAL SPECIFICATIONS



LP500M-423			
		ENGLISH METRIC	
A	Est. Configuration Length	ft m	60 18.3
B	Est. Configuration Width	ft m	12 3.7
C	Est. Configuration Height (without air bags)	ft m	13 3.9
	Est. Configuration Weight	tons tonnes	113 103
	Est. Power Consumption @ 85% Output	kW/hr	360

©2017 Milacron LLC. All Rights Reserved.
Pub Number: T4.1301.A.09.17

4165 Half Acre Rd.,
Batavia OH 45103
513.536.2000
info@milacron.com
www.milacron.com