

WARNING:**DISCONNECT MAIN POWER AT THE SOURCE PRIOR TO INSTALLATION****ONLY LICENSED ELECTRICIAN SHOULD PERFORM INSTALLATION****INSTALLATION INSTRUCTIONS**

Remove screws (F) to release J-box mounting plate (E). Use provided Wago connectors (B) to form electrical connection between the power supply (J) and AC wires coming from the J-box (A). Use the other pair of Wago connectors (C) to form electrical connection between the power supply (J) and the DC Jack (I) powering the lamp. Place all the connectors inside the J-box and use screws (D) to mount the J-box mounting plate (E) to the J-box. Attach the front cover plate (K) to the mounting plate (E) using provided screws (F). Thread the THIN lamp (G) into the lamp holder (L) and use the provided set screw (H) to lock the lamp into place. Insert the DC cable (I) into the plug located underneath the THIN Lamp and rotate the dimmer knob (M) to turn on the lamp.

KEEPING IT CLEAN

Gentle care is required in order to retain the quality metal finish of THIN Lamp for years to come. Like other natural metals, brass will patina over time, with natural yellow hues intensifying over time. Juniper protects its brass with a mild matte lacquer to delay coloration of the metal, and to protect it from exposure to humidity and natural oils.

In order to remove dirt, dust and fingerprints; gently wipe the lamp with a damp cloth. Do not use any chemical cleaning solutions; especially those containing ammonia, as this will damage the surface finish of the brass.

